

5-1/8" 10,000 psi Working Pressure Spherical Annular BOP

*****Increase your margins by Lowering your job costs****

This BOP has the following advantages when compared to using a larger sized annular BOP with a crossover spool on a 5-1/8" 10,000 psi BOP stack:

> Significant reduction in setup time

- More compact and lightweight
- o quicker connection to the stack
- lower mass warms up quicker

Reduced capital/rental costs

 Reduced hydraulic fluid volume requirements allow for a smaller, HPU (accumulator)

Reduced maintenance costs

- o minimal maintenance required
- o long lifespan of sealing element

> Increased safety

Full CSO (Complete Seal Off) @ MRWP

Technical Information:

Dimensions:

Height: 32" (811mm)
Diameter: 31.75" (807mm)
Weight: 4318 lbs (1959 kg)

Fluid Volumes:

Full Close: 4.8 US Gal (18.2 L)
Full Open: 4.1 US Gal (15.5 L)

Bore: 5-1/8"

Top Connection: 5-1/8" 10,000 psi studded with BX169 ring groove

Bottom Connection: 5-1/8" 10,000 psi flanged with BX169 ring groove

Temperature range T20: -20°F to 250°F (-20C to 121C)

NACE: MR0175 / ISO 15156

Manufactured and tested to meet the intent of API 16A

